



EP AMP 4 Compact Electric Utility Vehicle

Here is the answer for the professionals and organisations that are searching for a compact electric vehicle with great power, zero emission and a 4 person capacity.

This vehicle is ideal for light work and as a general transport vehicle. A small profile makes it perfect for transporting people in congested areas such as industrial sites and college campuses.

- Fully Road Legal
- In Cab Heater
- Air Conditioning
- Stereo System
- Alloy Wheels



Dimensions

Height	1700 mm
Length	2875 mm
Width	1380 mm
Gross Weight	795 kg
Turning Radius	5.6m
Climbing Ability	20%

Specification

Motor	60V / 4kw
Batteries	12v x 5
Charger	Onboard
Transaxle	12.49:1
Ground Clearance	145 mm
Braking Distance	4.5m

Performance

On Board Charger
AC Motor
4 Wheel Brakes
Battery Fill Kit
Full Light Kit
Digital Battery Gauge



ePowerTrucks (A Division of Lift Safe Ltd)

Unit 16 Hawksley Court, Hawksley Street Industrial Estate, Oldham, OL8 4PQ
0161 626 9628 | www.ePowerTrucks.co.uk | info@ePowerTrucks.co.uk

Full Specification List

Controller	Toyota 80L330B-330A	Seat	Blow moulding seat
Batteries	12v-150AH x 5	Floor	Aluminium non-slip flooring
Motor	AC 40v/5Kw	Body	PP plastic injected front, seat cask and body cover High strength carbon steel cage body
Charger	Onboard 60v/25A	Rear Mirror	Foldable external mirror
DC Converter	High Power 60v/12v-400Kw	Steering	Rack and pinion system
On Board Climate	Air Conditioner, Stroll Compressor, Refrigerating Unit 800w, Heating power 800w	Dashboard	Plastic moulded dash, combined liquid crystal instrument, electric lock, steering wheel lock, combination switch.
Windshield & Wiper	Car laminated glass, double speed wiper & washer	Lights & Signal	LED lights (dipped headlight, high light, turning light, backup light, position light, brake light) horn & reverse buzzer.
Roof	PP plastic injected roof with operable skylight	Brake System	Front disc, rear hub, double pipe, double circuit hydraulic brake & hand parking brake.
Front Suspension	McPherson independent suspension, cylinder hydraulic shock absorption	Rear Transaxle	Full body transaxle, gear ratio: 12.49:1, plate spring & telescopic shock absorber.
Tyre	155 65/R13	Overall Weight	795 kg
Height	1700 mm	Passenger Capacity	4
Length	2875 mm	Braking Stability	1770 mm
Width	1380 mm	Max Speed	25 mph
Ground Clearance	145 mm	Wheelbase	2200 mm
Energy Consumption	8.5 KwH (Per 100km)	Tread	Front 1170 mm Rear 1175 mm
Climbing Ability	20%	Braking Distance	<6m
Slope Ability	20%	Turning Radius	5.6m

ePowerTrucks (A Division of Lift Safe Ltd)

Unit 16 Hawksley Court, Hawksley Street Industrial Estate, Oldham, OL8 4PQ
0161 626 9628 | www.ePowerTrucks.co.uk | info@ePowerTrucks.co.uk